#### Golden Skies R/C Aircraft, Inc.®

Fuel Point™ - Medium

#### Installation Instructions

- Establish a relatively flat location on either the Cowl or Fuselage and drill a 3/8" hole.
- Size the hole to fit the Fuel Point™ Barrel as needed.
- Remove the mounting ring and insert the Fuel Point™
  barrel into the hole with the flange on the outside of the
  aircraft.
- Re-install the mounting Ring by screwing it onto the barrel from the back side and tighten. Use a tread locking material such as LocTite®271 or other suitable material.
- Insert the fuel line through the barrel from the back side and plug into the Fuel Point™ Plug nipple.
- Re-insert the Fuel Point™ Plug into the barrel fully.

## FUEL-POINT Medium



Mounting Ring



**Fuel-Point Barrel** 



Fuel-Point Plug

## Golden Skies R/C Aircraft, Inc.®

# Fuel Point™ - Large

#### **Installation Instructions**

- Establish a relatively flat location on either the Cowl or Fuselage and drill a 1/2" hole.
- Size the hole to fit the Fuel Point™ Barrel as needed.
- Remove the mounting screws and insert the Fuel Point™ Barrel
  into the hole from the outside of the aircraft.
- Orient the barrel so that one screw hole is directly at the top position. Use a felt-tip pen or other suitable marking device to mark the screw-hole locations on the aircraft side.
- Drill 5/64" holes into the aircraft for the mounting screws.
- Re-insert the fuel barrel into the ½" hole and slide the retaining ring onto the barrel from inside the aircraft.
- Attach the barrel to the ring using the five (5) screws provided in the kit. Use a tread locking material such as LocTite® 271 or other suitable material. Tighten securely.
- Thread the fuel or gas line through the barrel from the back side or inside of aircraft and plug onto the fuel plug nipple.
- "Plug" the Fuel Plug back into the Fuel Point™ barrel.
- Note: If the fuel plug's O-rings are too tight, add a very small amount of silicon grease to the O-ring as needed.
- Use the Gas Flag to indicate Gas Tank Status. (Full or to be filled)
  - O Pinch the sides of the gas flag to remove and put back on the plug.

Golden Skies R/C Aircraft, Inc.





Photos courtesy of Paul Moreau, Trabuco Flyers Club